



LAVE-VAISSELLE 500 AVEC ADOUCISSEUR ET POMPE DE VIDANGE INTÉGRÉS

- Châssis et paroi Acier Inox AISI 18/10
- Bras de lavage et de rinçage en inox
- Contact de sécurité-porte
- Porte en double paroi
- Résistance de cuve et surchauffeur Incoloy 800
- Rendement 20 casiers par heure
- Panier 500 x 500 mm
- Alimentation électrique 230 V / 50 Hz
- Résistance de la cuve 3 000 W
- Résistance du surchauffeur 3 000 W
- Doseur pour liquide de rinçage
- Protection contre la marche à sec
- Consommation d'eau : 4,5 litres
- Contenance de la cuve : 27 litres
- Raccord pour l'eau G3/4M
- Ecoulement Ø 28 mm
- Dotation 2 paniers
- Durée de cycle 180 secondes
- Puissance : 3 600 W
- Dimensions : L 570 x P 600 x H 834 mm
- Poids : 60 Kg

Référence article : CLVA50PVAD
EAN : 3611630000932

DISHWASHER 500 WITH WATER SOFTENER AND DRAIN PUMP

- Frame and wall in stainless steel AISI 18/10
- Wash arm
- Double wall door
- Superheater and tank heating element Incoloy 800
- Drain pump
- Water softener
- Protection against dry running
- Rinse aid dispenser
- Power of tank heating element: 3 kW
- Power of superheater: 3 kW
- Water connexion G3/4M
- Runoff: Ø 28 mm
- Water consumption: 4.5 liters
- Tank's capacity: 27 liters
- Performance: 20 baskets per hour
- Cycle duration: 180 seconds
- Basket: 500 x 500 mm
- Endowment: 2 baskets
- Electric supply: 230 V / 50 Hz
- Power: 3.6 kW
- Dimensions: W 570 x D 600 x H 834 mm
- Weight: 60 kg

Article reference : CLVA50PVAD
EAN : 3611630000932