



LAVASTOVIGLIE 500U

- Telaio e parete in acciaio inox AISI 18/10
- Bracci di lavaggio e risciacquo Acciaio inox
- Contatto di sicurezza della porta
- Porta a doppia parete
- Cesto 500 x 500 mm
- Riscaldatore del serbatoio e surriscaldatore Incoly 800
- Alimentazione 230 V 50Hz
- Riscaldatore del serbatoio 2.600 W
- Resistenza del surriscaldatore 2.500 W
- Consumo d'acqua 2 litri
- Capacità del serbatoio 24 litri
- Dosatori elettrici regolabili per detersivo e brillantante
- Attacco acqua G3/4M
- Uscita Ø 25 mm
- Produzione di 30 cassette all'ora
- Tempo di ciclo 120 secondi
- 2 cestini 500 x 500 mm, portaposate
- Potenza 3,12 kW / 230 V
- Dimensioni L 585 x P 600 x A 815 mm
- Peso 56 Kg

Riferimento articolo : CLVA50U
EAN : 3611630083614

DISHWASHER 500U

- Frame and wall AISI 18/10 stainless steel
- Washing and rinsing arms Stainless steel
- Door safety contact
- Double-walled door
- Basket 500 x 500 mm
- Tank heater and superheater Incoly 800
- Power supply 230 V 50 Hz
- Tank heater 2.600 W
- Superheater resistance 2.500 W
- Water consumption 2 liters
- Tank capacity 24 liters
- Adjustable electric detergent and rinse aid dosing units
- Water connection G3/4M
- Outlet Ø 25 mm
- Output 30 baskets per hour
- Cycle time 120 seconds
- 2 baskets 500 x 500 mm, cutlery holder
- Power 3 120 W / 230 V
- Dimensions W 585 x D 600 x H 815 mm
- Weight 56 kg

Article reference : CLVA50U
EAN : 3611630083614

04/05/2025

Questi dati possono essere modificati senza ulteriori informazioni. | These datas can be changed without further information.