



VAATWASSER 500U MET AFVOERPOMP EN WATERONTHARDER

- AISI 18/10 roestvrij stalen frame en wand
- Was- en spoelarmen roestvrij staal
- Deur veiligheidscontact
- Dubbelwandige deur
- Mand 500 x 500 mm
- Tankverwarming en oververhitter Incoly 800
- Stroomvoorziening 230 V 50Hz
- Tankverwarming 2.600 W
- Weerstand oververhitter 2.500 W
- Waterverbruik 2 liter
- Tankinhoud 24 liter
- Elektrisch regelbare wasmiddel- en spoelglansmiddelautomaten
- Trechter voor zout
- Wateraansluiting G3/4M
- Uitgang Ø 25 mm
- Capaciteit 40 kratten per uur
- Cyclustijd 120 seconden
- Uitrusting 2 korven 500 x 500 mm, 2 dekselhouders
- Vermogen 3 120 W / 230 V
- Afmetingen B 585 x D 600 x H 815 mm
- Gewicht 56 kg

Artikel referentie : CLVA50UPVA
EAN : 3611630083690

DISHWASHER 500U WITH DRAIN PUMP AND WATER SOFTENER

- Frame and wall AISI 18/10 stainless steel
- Washing and rinsing arms Stainless steel
- Door safety contact
- Double-walled door
- Basket 500 x 500 mm
- Tank heater and superheater Incoly 800
- Power supply 230 V 50 Hz
- Tank heater 2.600 W
- Superheater resistance 2.500 W
- Water consumption 2 liters
- Tank capacity 24 liters
- Adjustable electric detergent and rinse aid dosing units
- Salt funnel
- Water connection G3/4M
- Outlet Ø 25 mm
- Output 40 baskets per hour
- Cycle time 120 seconds
- Equipment 2 baskets 500 x 500 mm, 2 lid holders
- Power 3 120 W / 230 V
- Dimensions W 585 x D 600 x H 815 mm
- Weight 56 kg

Article reference : CLVA50UPVA
EAN : 3611630083690